

	Type	L #	Hits	Search Text	DBs
1	BRS	L1	8989	cleaning SAME rubber SAME (support or supporting or holdor holding or reinforce or reinforcing)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
2	BRS	L2	489	1 and thickness	USPAT
3	BRS	L3	168	2 and friction	USPAT
4	BRS	L4	50	3 and (vibrate or vibration)	USPAT
5	BRS	L9	50	4	USPAT
6	BRS	L10	2186	399/350,351.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
7	BRS	L11	549	10 and rubber	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
8	BRS	L12	549	11	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
9	BRS	L13	9	12 and (surface ADJ treated)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
10	BRS	L14	9	13	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
11	BRS	L16	10	(Cleaning WITH (surface ADJ treated) WITH friction)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
12	BRS	L18	1029	(Cleaning WITH (surface ADJ treated))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
13	BRS	L19	4	18 and (399/350,3512.ccls.)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
14	BRS	L20	4	19	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
15	BRS	L21	427	(Cleaning WITH (reduc\$5 ADJ friction))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
16	BRS	L22	45	21 and (399/350,3512.ccls.)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB
17	BRS	L26	39	blade NEAR5(surface ADJ treated)	USPAT
18	BRS	L27	39	26	USPAT
19	BRS	L28	463	18	USPAT
20	BRS	L29	7	18 and ("399"/\$.ccls.)	USPAT
21	BRS	L30	7	29	USPAT
22	BRS	L33	4	cleaning WITH reinforcing WITH thickness WITH (length or distance)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB